PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6: WO 97/37193 (11) International Publication Number: F41G 3/08 A1 (43) International Publication Date: 9 October 1997 (09.10.97) (21) International Application Number: PCT/GB96/00735 (81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, (22) International Filing Date: JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, 29 March 1996 (29.03.96) MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD. SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, (71) Applicant (for all designated States except US): ACCU-

RACY INTERNATIONAL LTD. [GB/GB]; P.O. Box 81, Portsmouth, Hampshire PO3 5SJ (GB).

(72) Inventor; and


(75) Inventor/Applicant (for US only): COOPER, Malcolm, D. [GB/GB]; Accuracy International Ltd., P.O. Box 81, Portsmouth, Hampshire PO3 5SJ (GB).

ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published

With international search report.

(54) Title: BALLISTIC CALCULATOR



(57) Abstract

A ballistic calculator, pocket sized, that when loaded with trajectory and wind drift data derived from firing tests, ballistic tables or computer predictions, will, when used in the field modify the data to give the user actual sight settings at each entry of site environmental and target orientation data requested in the display.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	18	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	It al y	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	zw	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

BALLISTIC CALCULATOR

This invention relates to a ballistic calculator for marksmen.

Many factors determine whether a target can be hit by a remote projectile fired from a hand held or hand supported weapon. These factors include range, temperature, air density, firing angle, wind strength and direction and drift due to spin stabilized bodies in air.

Up to now, hitting the target using such a weapon, especially at the longer ranges has been a hit or miss affair because :

- (a) No account is made of the variables, especially when moving from one venue to another.
- (b) Account is made of only some of the factors.
- (c) Some account of the factors is made by human 'guestimation'.
- (d) Detailed account is made by the use of complex tables which have generally fixed intervals involving time, clear thinking and extrapolation to obtain accuracy.
- (e) Detailed account is made by use of full sized computers, but use is limited by the fact that they cannot be taken into the field and therefore the programme input is not matched to the exact firing conditions.

According to the present invention there is provided a ballistic calculator that is a pocket sized, hand held electronic unit specifically designed to provide the marksman's sight settings for elevation and azimuth (windage) in angular MILS/MOA or 'clicks' according to the input of environmental conditions and target orientation at each firing sight.

The invention consists of a method of input, a memory, an electronic micro processor and an output display. The ballistic calculator is programmed using baseline data provided, input and stored from actual firing tests, computer ballistic data or ballistic tables for the particular weapon, sight and projectile to be used, at a site of known topographical and environmental conditions.

In the field, the micro processor calculates and displays in terms of sight settings, changes to the baseline trajectory and wind drift data as each piece of environmental or target orientation data is asked for in the 'prompt' display and entered.

Field use does not affect the stored baseline data.

Each Field use setting used can be stored for future recall should it be needed.

The ballistic calculator can be constructed to be used as a stand alone item, an item connected to various sensors for recording environmental, site and target orientation, as either above, but built into a sighting or weapon system as an integrated part of that system.

A specific embodiment of the invention will now be described by way of example with references to the accompanying drawing labeled Fig 1.

Fig 1 shows the face of the main panel of the calculator.


Referring to the drawing, the ballistic calculator comprises an environmentally sealed casing 1 containing the electronic circuitry micro processor, input keys, display and power service on function input key panel 2, used for loading the basic trajectory and wind ballistic data of the weapon, sight and projectile to be stored in the memory and a 'Field' numerical key panel 3 used at the firing site to input the requested environmental and target orientation information, requested in the 'Prompt' display 4, where the final sight corrections for elevation and windage will also be shown on completion of the calculations.

CLAIMS

- 1. A ballistic calculator that is a pocket sized, hand held electronic unit specifically designed to provide the marksman's sight settings for elevation and azimuth (windage) in angular MILS/MOA or 'clicks' according to the input of environmental conditions and target orientation at each firing sight.
- A ballistic calculator, as claimed in Claim 1, that is programmed/set up/calibrated prior to field use with trajectory and wind drift co-ordinates which are obtained from ballistic tables, computer programmes or live firing zeroing exercises.
- A ballistic calculator, as claimed in Claim 1 and Claim 2, that provides the 'come-ups' or 'setting' or 'elevation' in angular form or clicks from an established zero setting or base line which corresponds with the zero setting or base line in or on the sighting system.
- 4. A ballistic calculator, as claimed in Claim 1 or Claim 2 or Claim 3, that will provide a wind deflective readout in angular form or clicks with each elevation readout given.
- A ballistic calculator, as claimed in Claim 1, 2, 3 and 4 that will calculate and show an elevation and wind deflection readout at the input of any relevant information prompted, at each entry of relevant information requested or 'prompted'.
- 6. A ballistic calculator, as claimed in Claim 1, 2, 3, 4 and 5, that will automatically carry out computations to integrate drift caused by a spin stabilized projectile and show this in each readout.
- 7. A ballistic calculator, as claimed in Claim 1, that will record 'saved' data to memory for recall later.
- 8. A ballistic calculator, as claimed in Claim 1, wherein environmental gauges are built in and integrated with the microprocessor and these will include range, altitude, temperature, uphill/downhill angle and azimuth.
- A ballistic calculator, as claimed in Claim 1, wherein a 'hit probability' function is built in to the microprocessor.

10. A ballistic calculator, as claimed in Claim 1, wherein is built adaptation capability to be added in to or integrated with weapons, sighting systems or environmental measuring equipment.

1/1 **FIG**. **1**



INTERNATIONAL SEARCH REPORT

Inte onal Application No PCT/GB 96/00735

I PC 6	SIFICATION OF SUBJECT MATTER F41G3/08		
According	to International Patent Classification (IPC) or to both national of	elassification and IPC	
	DS SEARCHED		
IPC 6	documentation searched (classification system followed by classification s	fication symbols)	
Document	ation searched other than minimum documentation to the extent	that such documents are included in the fields	searched
Electronic	data base consulted during the international search (name of data	a base and, where practical, search terms used))
C. DOCU	MENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the	ne relevant passages	Relevant to claim No.
А	PATENT ABSTRACTS OF JAPAN vol. 18, no. 79 (M-1557), 9 Feb & JP,A,05 288495 (MITSUBISHI HE INDUSTRIES LIMITED), 2 Novembe see abstract; figure	AVY	1
А	PATENT ABSTRACTS OF JAPAN vol. 15, no. 318 (M-1146), 14 A & JP,A,03 117898 (MITSUBISHI EL CORPORATION), 20 May 1991, see abstract; figures	ugust 1991 ECTRIC	1
A	WO,A,87 01190 (SAAB INSTRUMENTS February 1987 see abstract see page 6, line 4 - page 10, l figures 1-6		1
Furth	ner documents are listed in the continuation of box C.	Patent family members are listed	in annex.
" Special cate	egories of cited documents:		
constae	int defining the general state of the art which is not red to be of particular relevance locument but published on or after the international	"T" later document published after the inte or priority date and not in conflict wi cited to understand the principle or th invention	th the application but
ming a	ate	"X" document of particular relevance; the cannot be considered novel or cannot	claimed invention
winch is	nt which may throw doubts on priority claim(s) or s cited to establish the publication date of another	'Y' document of particular relevance; the	curnent is taken alone
	or other special reason (as specified) nt referring to an oral disclosure, use, exhibition or	document is combined with one or mo	ventive step when the ore other such docu-
"P" documer	eans at published prior to the international filing date but an the priority date claimed	ments, such combination being obvious in the art.	is to a person skilled
	ctual completion of the international search	& document member of the same patent Date of mailing of the international sea	
	July 1996	1 4. 08. 96	e en report
Name and ma	ailing address of the ISA	Authorized officer	
	European Patent Office, P.B. 5818 Patentiaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016	Blondel, F	

INTERNATIONAL SEARCH REPORT

Information on patent family members

Internal Application No PCT/GB 96/00735

Patent document cited in search report	Publication	Patent	Publication	
	date	memb	date	
WO-A-8701190	26-02-87	SE-B- DE-A- EP-A- SE-A- US-A- US-A-	459209 3684326 0271493 8503860 4823674 4876942	12-06-89 16-04-92 22-06-88 20-02-87 25-04-89 31-10-89